

FESTO Semi-Rotary drive single acting DAPS



Characteristics

Series: DAPS

Function: Single acting

Housing material: Aluminium alloy

Operating temperature: -50 / 60 °C

Manufacturer ID	Cushioning	Construction size	Port Size in	Operating pressure bar	Article
DAPS-0015-090-RS4-F04	Without	15	G1/8	1 / 8.4	DAPS-0015-090-RS4-F04
DAPS-0015-090-RS4-F0305	Without	15	G1/8	1 / 8.4	DAPS-0015-090-RS4-F0305
DAPS-0030-090-RS1-F04	Without	30	G1/8	1 / 8.4	DAPS-0030-090-RS1-F04
DAPS-0030-090-RS2-F04	Without	30	G1/8	1 / 8.4	DAPS-0030-090-RS2-F04
DAPS-0030-090-RS1-F0507	Without	30	G1/8	1 / 8.4	DAPS-0030-090-RS1-F0507
DAPS-0030-090-RS4-F04	Without	30	G1/8	1 / 8.4	DAPS-0030-090-RS4-F04
DAPS-0053-090-RS2-F0507	Without	53	G1/8	1 / 8.4	DAPS-0053-090-RS2-F0507
DAPS-0053-090-RS4-F0507	Without	53	G1/8	1 / 8.4	DAPS-0053-090-RS4-F0507
DAPS-0120-090-RS4-F0710	Without	120	G1/8	1 / 8.4	DAPS-0120-090-RS4-F0710
DAPS-0180-090-RS4-F0710	Without	180	G1/8	1 / 8.4	DAPS-0180-090-RS4-F0710
DAPS-0720-090-RS4-F14-T6	Without	720	G1/4	3 / 8.4	DAPS-0720-090-RS4-F14-T6

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.